

According to Regulation (CE) n*830/2015 and n* 1907/2006

oduct FLUXO R175 AERO	Revision 4	Data	06.03.201	Deca	1 //
ILUXO KI75 ALKO	Revision 4	Date	00.03.201	9 Page	1/5
CTION 1 - IDENTIFICATION OF THE S	SUBSTANCE/MIXTURE AN	D OF T	НЕ СОМРА	NY	
1.1 Product Identifier					
Name of the product : FLU	XO R175 Aerosol				
1.2 <u>Relevant identified uses of the substan</u>	nce or mixture and uses advise	ed agair	<u>nst</u>		
Use : Deve	eloper for Penetrant Testing				
1.3 Details of the Supplier of the Safety D	Data Sheet				
Manufacturer and Supplier: SREM TECHNOLOGIES					
14, rue des frères Chappe	Tél : +33 (0)2.43.48.15.10				
ZI Ouest	Fax : +33 (0)2.43.45.25.26				
72200 La FLECHE - FRANCE	e-mail : <u>info@sre</u>	<u>m.fr</u>	WWV	v.srem.fr	
1.4 Emergency Telephone Number					
Emergency Telephone Number	: INRS +33.(0)1.45.42.59.5	59			
CTION 2 – HAZARDS IDENTIFICATIO	N				
2.1 <u>Classification of the substance or Mix</u>		1 4			
Flammable Aerosol, Cat 1 Eye Irrit, Cat 2	H222: Extremely Flammab H229 : Pressurised contained			d	
STOT SE, Cat 3	H319 : Causes serious eye			u	
	H336 : May cause drowsing				
2.2 Labels Elements					
Hazards Pictograms					
Hazard Statement		•			
H222 : Extremely Flammable Aerosol					
H229 : Pressurised container : May burs	st if heated				
H319 : Causes serious eye irritation					
H336 : May cause drowsiness or dizzine	ess				
Precautionary Statement					
P210 Keep away from heat, hot surfaces		ignition	sources. No s	moking.	
P261 Avoid breathing dust/fume/gas/mi	st/vapours/spray.				

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P501 Dispose of contents/container to an approval waste disposal plant.

Special labelling for aerosol cans:

Pressurized container: Do not pierce or burn, even after use - Protect from sunlight - Do not expose to temperatures exceeding $50^{\circ}C$ - Do not spray on an open flame or other ignition source - Keep away from heat/sparks/open flames/hot surfaces - No smoking.

2.3 Other Hazards



According to Regulation (CE) n[•]830/2015 and n[•] 1907/2006



Product FLUXO R175 AERO

Revision 4

06.03.2019 Date

Page

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Mixtures

Substance Name	N° CAS N° CE	Classification (1272/2008)	Concentration (%)
Propellant : Propane Butane	74-98-6 - 200-827-9 01-2119486944-21 106-97-8 - 203-448-7 01-2119474691-32	Flam. Gas 1 H220 Press. Gas	> 30
Propan-2-ol	67-63-0 200-661-7 01-2119457558-25-	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336	50 à 75 %

Full Test of H phrases: see section 16.

SECTION 4 – FISRT AID MEASURES

4.1 Description of first aid measures

General information	Take off immediately all contaminated clothing and wash it before reuse. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If unconscious place in recovery position and seek medical advice.
After ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell.
After eye contact	In case of eye irritation consult an ophthalmologist. Rinse immediately carefully and thoroughly with eye-bath or water.
After skin contact	After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation. Consult a physician. Take off immediately all contaminated clothing.
Following inhalation	In case of inhaling spray mist, consult a doctor immediately and show him packing or label. If breathing is irregular or stopped, administer artificial respiration.

4.2 Most important symptoms and effects, both acute and delayed

Respiratory complaints Drowsiness

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5 – FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water spray Water mist Foam Extinguishing powder Unsuitable extinguishing media: Full Water Jet

5.2 Special Hazards arising from the substance or mixtures


: In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide.

5.3 Advice for Firefighters

: In case of fire: Wear self-contained breathing apparatus.



According to Regulation (CE) n*830/2015 and n* 1907/2006



7.1 Precautions for sage handling

All work processes must always be designed so that the following is excluded: Inhalation Skin contact Eye contact Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2 Conditions for safe storage, including any incompatibilities

Ensure adequate ventilation of the storage area. Hints on storage assembly: Materials to avoid oxidizing agent Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place.

7.3 Specific End Uses

: Developer for Penetrant Testing

SECTION 8 - EXPOSURE CONTROLES AND PERSONAL PROTECTION

8.1 <u>Control Parameters</u>

Component	CAS	
Propan-2-ol	67-63-0	Short Term Value = 400 ppm
Butane	106-97-8	Long Term Value = 800 ppm = 1900 mg/m3

8.2 Exposure Controls

Eye/face protection	: Suitable eye protection: Eye glasses
Skin protection	: Use protective skin cream before handling the product. Hand protection
	Suitable gloves type: NBR (Nitrile rubber)
Respiratory protection	: Filter type: AX is appropriate (if necessary).
Protective clothing	: Body protection: not required.
	General health and safety measures: When using do not eat, drink, smoke, sniff.
	Wash hands before breaks and after work. After cleaning apply high-fat content
	skin care cream.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemicals properties:

Physical Sate	: Aerosol
Aspect	: White liquid



According to Regulation (CE) n*830/2015 and n* 1907/2006

Product	FLUXO R175 AERO	Revision 4	Date	06.03.2019	Page	4/5
	Odor	: characteristic				
	Density (active component)	: 890 kg/m ³				
	Flash Point (active component)	: <12°C				
	Ignition Temperature	:>250°C (ASTM E65	59)			
	Explosive Limits	: lower : 2%	upper : 12%			
	Solubility	: not soluble in water				

9.2 Others information

SECTION 10 - STABILITY AND REACTIVITY

10.1 <u>Reactivity</u>	
	: Reaction with oxidising agent
10.2 <u>Chemical Stability</u>	
	: Stable in normal condition of use
10.3 <u>Possibility of Hazardous rea</u>	<u>ctions</u>
	: No Data available
10.4 <u>Conditions to avoid</u>	
	: No Data available
10.5 <u>Incompatible Materials</u>	
	: No Data available
10.6 <u>Hazardous decomposition p</u>	<u>roducts</u>
	: No Data available

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Information

Component	DL50 Oral	DL50 Dermal	CL50 Inhalation
Propan-2-ol	5 840 mg/kg (rat)	13 900 mg/kg (rabbit)	> 25000 mg/L (rat)

Acute oral toxicity: Data apply to the main component. Acute dermal toxicity: Data apply to the main component. Acute inhalation toxicity: Data apply to the main component.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 Toxicity

Component	EL50 (24h) daphnie	LL50 (96h) fish
Propan-2-ol	9740 mg/L	9 640 mg/L

12.2 Persistence and degradability

: No Data available

12.3 Bio accumulative potential

: No Data available

12.4 Mobility in soil

: No Data available

12.5 Results of PBT and vPvB assessment

: no PBT and vPvB



According to Regulation (CE) n*830/2015 and n* 1907/2006



Product FLUXO R175 AERO

Revision 4

Date **06.**

06.03.2019 Page

5/5

12.6 Other adverse effects

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 Waste Treatment methods

Do not reject the product Ensure conformity to local disposal regulations. Packing is not taken again, they must be eliminated (polyethylene cans)

SECTION 14 – TRANSPORT INFORMATION

14.1 <u>UN Number</u>

		1950
14.2	<u>UN proper shipping name</u>	
		AÉROSOLS, FLAMMABLE
14.3	<u>Transport Hazard Class</u>	
		ADR / RID : 2
		IMDG:2
		IATA : 2.1
14.4	Packing Group	
		ADR / RID : No - Instruction LQ2 (LIMITED QUANTITY)
		IMDG : No - Instruction LQ2 (LIMITED QUANTITY)
		IATA :
14.5	Environmental hazards	
		No

14.6 Special precautions for users

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

SECTION 15 - REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance/mixture

15.2 Chemical Safety Assessment

: No data available

SECTION 16 – OTHER INFORMATION

The European regulation imposes that all the H sentences (section 2) appear in this paragraph. According to their concentration in the final product, these sentences do not appear on the label. This is why sentences or initials appearing in this paragraph can not appear on the label.

H sentences (section 2 and 3)

H220 : Extremely flammable Gas

- H222 : Extremely Flammable Aerosol
- H225 : Highly flammable liquid and vapour
- H229 : Pressurised container : May burst if heated
- H319 : Causes serious eye irritation
- H336 : May cause drowsiness or dizziness

: Please refer to Technical Data Sheet