

SAFETY DATA SHEET

According to Regulation (CE) n\*830/2015 and n\* 1907/2006

	Revision 4 Date	06.03.2019 Page 1/
CTION 1 - IDENTIFICATION OF TH	IE SUBSTANCE/MIXTURE AND OF	THE COMPANY
1.1 <u>Product Identifier</u>		
Name of the product : F	LUXO S190 Aerosol	
1.2 <u>Relevant identified uses of the sub</u>	stance or mixture and uses advised aga	inst
Use : S	solvent for Penetrant Testing	
1.3 Details of the Supplier of the Safe	ty Data Sheet	
Manufacturer and Supplier: SREM TECHNOLOGIES		
14, rue des frères Chappe	Tél : +33 (0)2.43.48.15.10	
ZI Ouest	Fax : +33 (0)2.43.45.25.26	
72200 La FLECHE - FRANCE	e-mail : <u>info@srem.fr</u>	www.srem.fr
1.4 Emergency Telephone Number		
Emergency Telephone Number	: INRS +33.(0)1.45.42.59.59	
	<u>Mixture</u> H222: Extremely Flammable Aer	osol
Flammable Aerosol, Cat 1 Skin Sens, Cat 2 STOT SE, Cat 3		y burst if heated lizziness
Flammable Aerosol, Cat 1 Skin Sens, Cat 2 STOT SE, Cat 3 Aquatic Chronic 2	H222: Extremely Flammable Aer H229: Pressurised container : Ma H315: Causes skin irritation H336: May cause drowsiness or c	y burst if heated lizziness
Flammable Aerosol, Cat 1 Skin Sens, Cat 2 STOT SE, Cat 3 Aquatic Chronic 2 2.2 <u>Labels Elements</u> Hazards Pictograms	H222: Extremely Flammable Aer H229: Pressurised container : Ma H315: Causes skin irritation H336: May cause drowsiness or c	y burst if heated lizziness
<ul> <li>Flammable Aerosol, Cat 1</li> <li>Skin Sens, Cat 2</li> <li>STOT SE, Cat 3</li> <li>Aquatic Chronic 2</li> </ul> 2.2 Labels Elements Hazards Pictograms Hazard Statement <ul> <li>H222 : Extremely Flammable Aeros</li> <li>H229 : Pressurised container : May</li> </ul>	H222: Extremely Flammable Aer H229: Pressurised container : Ma H315: Causes skin irritation H336: May cause drowsiness or o H411: Toxic to aquatic life with long	y burst if heated lizziness
	H222: Extremely Flammable Aer H229: Pressurised container : Ma H315: Causes skin irritation H336: May cause drowsiness or o H411: Toxic to aquatic life with long	y burst if heated lizziness

present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P501 Dispose of contents/container to an approval waste disposal plant.

### **Special labelling for aerosol cans:**

Pressurized container: Do not pierce or burn, even after use - Protect from sunlight - Do not expose to temperatures exceeding 50°C - Do not spray on an open flame or other ignition source - Keep away from heat/sparks/open flames/hot surfaces - No smoking.

#### 2.3 Other Hazards



SAFETY DATA SHEET

According to Regulation (CE) n\*830/2015 and n\* 1907/2006



# Product FLUXO S190 AERO

**Revision 4** 

06.03.2019 Date

Page

### **SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

# 3.1 Mixtures

Substance Name	N° CAS N° CE	Classification (1272/2008)	Concentration (%)
Propellant : Propane Butane	74-98-6 - 200-827-9 01-2119486944-21 106-97-8 - 203-448-7 01-2119474691-32	Flam. Gas 1 H220 Press. Gas	> 30 %
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4 01-2119475515-33-xxxx	Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	> 50 %

Full Test of H phrases: see section 16.

# **SECTION 4 – FISRT AID MEASURES**

#### 4.1 Description of first aid measures

General information	Take off immediately all contaminated clothing and wash it before reuse. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If unconscious place in recovery position and seek medical advice.
After ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell.
After eye contact	In case of eye irritation consult an ophthalmologist. Rinse immediately carefully and thoroughly with eye-bath or water.
After skin contact	After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation. Consult a physician. Take off immediately all contaminated clothing.
Following inhalation	In case of inhaling spray mist, consult a doctor immediately and show him packing or label. If breathing is irregular or stopped, administer artificial respiration.

# 4.2 Most important symptoms and effects, both acute and delayed

**Respiratory complaints Drowsiness** 

# 4.3 Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5 – FIREFIGHTING MEASURES**

# 5.1 Extinguishing media

Suitable extinguishing media: Water spray Water mist Foam Extinguishing powder Unsuitable extinguishing media: Full Water Jet

#### 5.2 Special Hazards arising from the substance or mixtures

: In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide.

5.3 Advice for Firefighters


: In case of fire: Wear self-contained breathing apparatus.



Product

SAFETY DATA SHEET

According to Regulation (CE) n\*830/2015 and n\* 1907/2006



: Do not allow to enter into surface water or drains

### 6.3 Methods and material for containment and cleaning up

: Absorb with liquid-binding material

### 6.4 Reference to others sections

6.2 Environmental Precautions

: See section 8 & 13

### **SECTION 7 – HANDLING AND STORAGE**

# 7.1 Precautions for sage handling All work processes must always be designed so that the following is excluded: Inhalation Skin contact Eye contact Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2 Conditions for safe storage, including any incompatibilities Ensure adequate ventilation of the storage area. Hints on storage assembly: Materials to avoid oxidizing agent Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place.

### 7.3 Specific End Uses

: Solvent for Penetrant Testing

### SECTION 8 - EXPOSURE CONTROLES AND PERSONAL PROTECTION

### 8.1 Control Parameters

Component	CAS	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	142-82-5	Short Term Value = 500 ppm
Butane	106-97-8	Long Term Value = 800 ppm = 1900 mg/m3

### 8.2 Exposure Controls

Eye/face protection	: Suitable eye protection: Eye glasses
Skin protection	: Use protective skin cream before handling the product. Hand protection
	Suitable gloves type: NBR (Nitrile rubber)
Respiratory protection	: Filter type: AX is appropriate (if necessary).
Protective clothing	: Body protection: not required.
	General health and safety measures: When using do not eat, drink, smoke, sniff.
	Wash hands before breaks and after work. After cleaning apply high-fat content
	skin care cream.

# **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 Information on basic physical and chemicals properties:

Physical Sate	: Aerosol
Aspect	: Liquid
Odor	: characteristic



SAFETY DATA SHEET

According to Regulation (CE) n\*830/2015 and n\* 1907/2006

Product	FLUXO S190 AERO	Revision 4	Date	06.03.2019	Page	4/5	
	Density (active component) Flash Point (active component) Ignition Temperature Explosive Limits Solubility	: 760 kg/m <sup>3</sup> : -4°C : > 400°C (ASTM E6 : lower : 1% : soluble in water	559) upper : 6.7%				
9.2 <u>Ot</u>	hers information						
SECTION	<b>10 - STABILITY AND REACTI</b>	VITY					
10.1 <u>Re</u>	eactivity : Rea	ction with oxidising ager	nt				
10.2 <u>Cł</u>	nemical Stability		_				
10.2 Da		le in normal condition of	fuse				
10.5 <u>P0</u>	<u>ssibility of Hazardous reactions</u> : No I	Data available					
	10.4 <u>Conditions to avoid</u> : No Data available						
10.5 <u>In</u>	10.5 <u>Incompatible Materials</u>						
10.6 Ha	: No Data available 10.6 Hazardous decomposition products						
1010 11		Data available					
SECTION	11 - TOXICOLOGICAL INFOR	MATION					

### 11.1 Information on Toxicological Information

Component	DL50 Oral	DL50 Dermal	CL50 Inhalation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	17 000 mg/kg (rat)	$> 2\ 000\ mg/kg\ (rabbit)$	60 mg/L (rat)

Acute oral toxicity: Data apply to the main component. Acute dermal toxicity: Data apply to the main component. Acute inhalation toxicity: Data apply to the main component.

### SECTION 12 – ECOLOGICAL INFORMATION

### 12.1 Toxicity

	Component	EL50 (24h) daphnie	LL50 (96h) fish			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	1,5 mg/L	10mg/L			
12.2 Persistence and degradability						
	: No Data	available				
12.3 <u>Bio accumulative potential</u>						
	: No Data available					
12.4 Mobility in soil						

- : No Data available
- 12.5 <u>Results of PBT and vPvB assessment</u>
  - : no PBT and vPvB
- 12.6 Other adverse effects



SAFETY DATA SHEET

According to Regulation (CE) n\*830/2015 and n\* 1907/2006

Product	FLUXO S190 AERO	Revision 4	Date	06.03.2019	Page	5/5		
SECTION	SECTION 13 – DISPOSAL CONSIDERATIONS							
<b>13.1</b> <u>Waste Treatment methods</u> Do not reject the product Ensure conformity to local disposal regulations. Packing is not taken again, they must be eliminated (polyethylene cans)								
SECTION	14 – TRANSPORT INFOR	MATION						
14.1 <u>U</u>	N Number							
		1950						
14.2 <u>U</u>	N proper shipping name	AÉROSOLS, FLAMMABLE						
14.3 <u>T</u>	ransport Hazard Class							
		ADR / RID : 2						
		IMDG:2						
		IATA : 2.1						
14.4 <u>P</u>	acking Group							
		ADR / RID : No - Instruction LQ2		- /				
		IMDG : No - Instruction LQ2 (LIN	MITED Q	UANITTY)				
145 E	nvironmental hazards	IATA :						
14.5 <u>E</u>	Invironmental nazarus	No						
14.6 <u>S</u>	pecial precautions for users	110						

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

### **SECTION 15 – REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations/legislation specific for the substance/mixture

15.2 Chemical Safety Assessment

: No data available

### **SECTION 16 – OTHER INFORMATION**

The European regulation imposes that all the H sentences (section 2) appear in this paragraph. According to their concentration in the final product, these sentences do not appear on the label. This is why sentences or initials appearing in this paragraph can not appear on the label.

#### H sentences (section 2 and 3)

H220: Extremely flammable Gas

- H222: Extremely Flammable Aerosol
- H225: Highly flammable liquid and vapour
- H229: Pressurised container: May burst if heated
- H304: May be fatal if swallowed and enters airways
- H315: Causes skin irritation
- H336: May cause drowsiness or dizziness
- H400: Very toxic to aquatic life
- H410: Very toxic to aquatic life with long lasting effects
- H411: Toxic to aquatic life with long lasting effects

: Please refer to Technical Data Sheet