



FLUXO P125

Water Washable Red Dye Penetrant - Sensitivity Level 2

General Appearance & Composition

- Water Washable and Solvent Removable Red Dye Penetrant
- Method A/C Type 2 Level 2 according to EN ISO 3452
- Low level of background / excellent washability
- FLUXO P125 is a stable solution of petroleum distillates (high flash point), nonionic surfactants and red dyes.
- Processing Temperature: 0° to 50°C
- Associated products:
 - Cleaner / Remover: FLUXO S190 / FLUXO N130
 - Solvent Based Developer: FLUXO R175 FLUXO R180
- Manufacturer: SREM TECHNOLOGIES

Approval & Specifications

- Sensitivity Level 2 according EN ISO 3452-2
- EN ISO 3452-2
- EN ISO 3452-6 (Low temperature)
- RCC-M Code
- ASME Boiler and Pressure Vessel Code Section V
- ASTM E 1417 ASTM E 165
- Low in Sulphur & Halogens (Nuclear Quality)
- PMUC Can be used in nuclear plants

Properties

- Aspect: Red Liquid
- Density (20°C): 0,855
- Flash Point: > 82°C
- <u>Viscosity</u>: 3 mm²/s (40°C)
- Compatible with any metal & many synthetic materials

Instructions for Use

- <u>Cleaning:</u> Remove rust, tinder and all contaminations from the part with FLUXO cleaner
- <u>Application of Penetrant:</u> Apply FLUXO P125: Application by immersion, spraying, brushing, dipping, etc... Allow to penetrate for at least 10 minutes.
- Removal: Remove the excess penetrant from the surface, with water. If you can't or don't want to use water, remove the excess penetrant with solvent FLUXO S190 or remover FLUXO N130.
- <u>Drying:</u> Begin drying procedure immediately after water wash.
- <u>Developing:</u> Apply FLUXO developer on the part, achieving a thin and uniform layer.
- <u>Inspection:</u> Parts shall be inspected as per ISO 3059 standard requirements. Surface defects will appear as red indication.

Shelf Life

- Minimum of 5 years, stored at room temperature.
- Please refer to the Safety Data Sheet

Pack Sizes

- Aerosol Can 500mL
- Drum 1L 5L 10L 200L



Version: 09/2021